

HM 10 - 500 KTL

HM 14 - 800 KTL

Specifications

Infeed height:	800 mm
Ejection height:	up to 5.660 mm
Transport height:	3.650 mm
Transport width:	2.980 mm
Working height:	1.510 mm
Working width:	4.300 mm
Conveyor belt:	900 mm
Infeed table length:	1.500 mm
Standard-sieve:	45/60 mm
Pressure roller Ø:	800 mm
Chipping drum Ø:	495 mm
Flywheel Ø:	1.370 mm
Flywheel mass:	1.000 kg

HM 10 - 500 KTL

Infeed width:	877 mm
Length:	4.740 mm
Support load:	1.400 kg
Weight:	13.100 kg

HM 14 - 800 KTL

Infeed width:	1.215 mm
Length:	5.080 mm
Support load:	1.500 kg
Weight:	14.500 kg

Chassis

- Chassis-tandem 40/60 km/h with dual line air brakes
- Tyres:
 - » 385/55 R22.5
 - » 400/55 22.5
 - » 560/45 R22.5
- Height of towing port:
 - » 500 mm » 650 mm
 - » 720 mm » 1.000 mm



HIGHLIGHTS



Discharging chute telescopic



Special-sieve with stop-bars



3 cross augers



*Rotor cover
with extra sieve*



*Automatic trailer coupling
with compressed air connection*

