

Line, Tie and Lacing Wires

Suitable for a variety of commercial applications, Hampton's coiled wire is available in a wide choice of specifications, grades and finishes.

	Typical Coil Weights (kg)					Typical Coil Lengths (metres)				
Galvanised Class A Soft: 350-550 N/mm ²	25	10	5	1	0.5	78	65	52	39	26
1.60mm	✓	✓	✓	✓	✓					
1.90mm	✓	✓	✓	✓	✓					
2.00mm	✓	✓	✓	✓		✓		✓		
2.50mm	✓	✓	✓			✓	✓	✓	✓	✓
3.00mm	✓	✓	✓			✓		✓		
3.15mm	✓	✓	✓			✓	✓	✓	✓	✓
3.55mm	✓	✓	✓			✓	✓	✓	✓	✓
4.00mm	✓	✓	✓							
5.00mm	✓	✓	✓							
6.00mm	✓	✓	✓							
Hard: 600-800 N/mm ²										
2.00mm	✓	✓	✓							
2.50mm	✓	✓	✓							
3.00mm	✓	✓	✓							
3.15mm	✓	✓	✓							
4.00mm	✓	✓	✓							
High Tensile: 1050 N/mm ² (min)										
1.60mm	✓	✓	✓							
2.00mm	✓	✓	✓							
2.50mm	✓	✓	✓							
3.15mm	✓	✓	✓							
Galvanised Class D Soft: 350-550 N/mm ²										
0.90mm	✓	✓	✓	✓	✓					
1.00mm	✓	✓	✓	✓	✓					
1.25mm	✓	✓	✓	✓	✓					
1.70mm	✓	✓	✓	✓	✓					
2.00mm	✓	✓	✓	✓	✓					

Galvanised Wire

- Wire produced to BS 4102
- Galvanised to BS EN 10244-2
- Available in a choice of specifications
- Easy to handle
- Choice of coil weights

Plastic Coated Wire

- Core wire manufactured to BS 4102
- Galvanised to BS EN 10244-2 Class D as standard
- Green or Black plastic coated as standard

