

# Horizontal splitter 28 tons on 3-point hitch - H28 series


SPLITTING RANGE

## Horizontal splitter 28 tons on 3-point hitch

- Splitting length : 120 cm
- 6 - splitting knife as option

### Hydraulic log winch with remote control for H28


- This option can be assembled in the factory or afterwards with our kits.
- Traction power : 600 kg
  - Cable : 20 m length Ø 6 mm
  - Cable average speed : 0.5 m/s - Adjustable
  - 12 V from tractor required
  - Safety switch at the end of winding
  - Automatic regulation system at splitting speed



Ø 110 cm  
< 120 cm >



VIDEO ON  
WWW.A-M-R.FR



3-points linkage



6 - splitting knife

Log splitter	HPF28	HEL28	HPE28
Splitting force (to)	28	28	28
Splitting length (cm)	120	120	120
Pump	Double	Triple	Double/Triple
Power supply	PTO tractor	400 V / 9,2 kW	PTO tractor + Elec. 400 V
Automatic speed (cm/s)	24,0	22,7	24,0 / 22,7
Retun speed (cm/s)	21,8	16,2	21,8 / 16,2
Oil tank capacity (L)	85	85	85
Pump output (L/min)	89	87,8	89 / 87,8
Dimension (HxLxW cm)	( Transport position ) : 194 x 178 x 325 / ( Working position ) : 133 x 226 x 405		
Weight (kg)	1091	1110	1200

Log winch can be assembled in the factory or afterwards with our kits.

12 V necessary

6 - way splitting knife ( FCX001001 )

Log winch with remote control for 28 tons ( TTB000303 )

PTO shaft type 3 ( CAR00001A )

Lighting with support for H28 on 3-point hitch ( RAM00200 )