

# Road homologated splitter 13/17 tons- VMR Series

SPLITTING RANGE



## VMR 13-17 series

VMR13-17 splitters on a road-homologated frame. They combine effectiveness and robustness and stand for great mobility and autonomy.

- Comfort : hydraulic tilting splitter in working and transport position
- 2-handle control
- 2 splitting speeds
- Road homologation according to directive 2007/46 / EC
- Electric start on diesel engine
- 115 cm cutting length
- Adjustable claw to hold all logs ( *from 8cm* )
- Log support arm with adjustable claw for wood and sappie support
- Mechanical log-lift included ( *really convenient* )
- Non-skid plate in full steel with angled edges to facilitate timber handling
- Cylinder retractable without tools



17 To Ø 80 cm  
< 110 cm >



13 To Ø 70 cm  
< 110 cm >



VMR17ESS



Anti-theft system (option)



Spare wheel (option)

Log splitter	VMR13ESS-9DP	VMR17ESS-9DP	VMR17ESS-13DP	VMR17DIE DP
Road homologation according to directive 2007/46 / EC ( <i>additional fee</i> )				
Splitting force (to)	13	17	17	17
Splitting length (cm)	115	115	115	115
Pump	Double	Double	Double	Double
Power supply	Petrol Honda 9 HP	Petrol Honda 9 HP	Petrol Honda 13 HP	Diesel 9 HP
Fuel capacity	5.3 L	5.3 L	6.1 L	5.5 L
Speed 1 (cm/s)	9,5	9,1	9,1	9,1
Speed 2 (cm/s)	25,5	20,3	20,3	20,3
Return speed (cm/s)	15,2	12,8	12,8	12,8
Oil capacity (L)	24	24	24	24
Pump output (L/min)	36,2	36,2	36,2	36,2
Dimension (HxLxW cm)	( <i>Transport position</i> ) : 195 x 126 x 303 / ( <i>Work position</i> ) : 260 x 126 x 318			
Weight (kg)	520	550	550	600
According to the standards, it's not allowed to use a winch on this kind of equipment	Extra charge for chassis with brake for parking			
	Hydraulic log-lift for VMR13/17 ( LBH001100 )			
	Spare wheel with support ( SUP00011 )			
	Anti-theft system ( ANT00005 )			