


LHT8/80/15 STOCK FENCE



Hinge joint

Traditional cost-effective joint. Enables the netting to be turned out or cranked for use in special applications.

Description

LHT8/80/15 is a lightweight, high tensile stock fence, commonly used as an economical solution in areas of low pressure from livestock or for a short to medium term project. Tornado LHT Fence is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering so does not need to be retightened annually.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Two strands of barbed wire or a single electrified wire can be added to the top of the fence. For more information on installation please refer to BS1722 part 2.

Suitable For

Short to medium term Livestock fencing

Low-pressure Livestock fencing

Specification

Number of line wires	8
Overall height	80cm
Distance between stay wires	15cm
Top & bottom line wire specification	2mm diameter - 1100 - 1250 N/mm ²
Intermediate line wire specification	2mm diameter - 1100 - 1250 N/mm ²
Vertical stay wire specification	2mm diameter - 695 - 850 N/mm ²
Approx. weight per 100m roll	38kg
Material composition	Heavily galvanised steel wire

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

LHT8/80/15 STOCK FENCE

British & European Standards

- BS EN 10218** Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.
- BS EN 10223** Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.
- BS EN 10244** Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).
- BS EN ISO9001** Tornado Wire Ltd operates a quality management system certified to this standard.

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Health & Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Product Codes

100m roll HZLH088001

250m roll* HZLH088004

*Minimum order quantity may apply.

