

Unique log grapple with tilt function

- Developed to make logging more efficient.

The T220 tilt grapple is a normal loading grapple with built-in tilt function, but still works with the same hydraulics as a traditional loading grapple. You only need 2 hydraulic lines (grapple open/close). The tilt function is controlled wirelessly. Two extra control buttons/pedals (tilt up/tilt down) are included in the delivery. These control buttons can be installed in a suitable place. 2 batteries and a battery charger are also included in the delivery.



FEATURES

Fast and easy to use - increases productivity

Stable both in felling and loading position

Easy to install

No additional hydraulic lines are needed - only grapple open and grapple close

Completely stepless control - for example, stop the tilt half way if necessary

Control system alternatives

Standard: 1 double-acting hydraulic line, grapple open/close + Remote control for tilt function

Grapple claw alternatives

Standard: Traditional log grapple claws (closed ends)

Option: Energy grapple claws (open ended)

Option: A-model claws (with diagonal plates)

Technical information

| | |
|-----------------------|---------------------|
| Model | T220 <i>G2</i> |
| Grapple size | 0,22 m ² |
| Weight | 155 kg |
| Rec. working pressure | 200-230 bar |
| Rec. oil flow rate | 30 - 50 l/min. |
| Opening of grapple | 1200 mm |
| Attachment standard | 173/6 |