


TORNADO®

R12/110/5 HORSE FENCE



Torus Knot

Manufactured with a high pressure bonded, smooth knot and a continuous vertical stay wire. The Tornado Torus offers optimal strength even in the most extreme environments.

Description

R12/110/5 Horse Fence has pre-stripped ends for ease of joining. It features solid vertical wires, close vertical wire spacings to help prevent damage to hooves, and the unobtrusive high pressure bonded Torus knot which does not have any sharp edges. Tornado Torus Horse Fence is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering so does not need to be retightened annually.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Recommended use with Centaur, rail or lightning to add additional height and visibility. For more information on installation please refer to BS1722 part 2

Suitable For

Horse Fencing

Specification

Number of line wires	12
Overall height	110cm
Distance between stay wires	5cm
Top & bottom line wire specification	2.5mm diameter - 1235 - 1390 N/mm ²
Intermediate line wire specification	2.5mm diameter - 1235 - 1390 N/mm ²
Vertical stay wire specification	2.5mm diameter - 695 - 850 N/mm ²
Approx. weight per 50m roll	78.86kg
Material composition	Heavily galvanised steel wire

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

TORNADO®

Latest update: 08/10/20

sales@tornadowire.com

Tel: +44 (0) 1789 778 766



INVESTORS
IN PEOPLE | Gold

TORNADO®

R12/110/5 HORSE FENCE

British & European Standards

- BSEN 10218** Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.
- BSEN 10223** Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.
- BSEN 10244** Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).
- BS EN ISO9001** Tornado Wire Ltd operates a quality management system certified to this standard.

Sustainability

All Tornado products are 100% recyclable.

Traceability


This fence is batch marked and can be traced back to point of manufacture.

Health & Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Product Codes

50m roll RZST121101



Tornado Wire Limited, Bidford-on-Avon, Alcester, Warwickshire, B50 4JH. Tel: +44 (0) 01789 778 766 | www.tornadowire.com | email: sales@tornadowire.com

TORNADO®

Latest update: 08/10/20

sales@tornadowire.com

Tel: +44 (0) 1789 778 766



INVESTORS IN PEOPLE | Gold